


RADIO RECEIVER ASSY REPLACEMENT

670K8-01

HINT:


COMPONENTS: See page 67-2

1. REMOVE INSTRUMENT PANEL FINISH PLATE(See page 71-12)
2. REMOVE INSTRUMENT PANEL FINISH PANEL SUB-ASSY LOWER(See page 71-12)
3. REMOVE INSTRUMENT CLUSTER FINISH PANEL SUB-ASSY(See page 71-12)
4. REMOVE CONSOLE UPPER REAR PANEL SUB-ASSY(See page 71-12)
5. REMOVE CONSOLE PANEL SUB-ASSY UPPER(See page 71-12)
6. REMOVE AIR CONDITIONING CONTROL ASSY(See page 71-12)
7. REMOVE INSTRUMENT CLUSTER FINISH PANEL SUB-ASSY CENTER(See page 71-12)




8. REMOVE RADIO RECEIVER ASSEMBLY W/BRACKET

- (a) Remove the 2 bolts.
- (b) Disconnect the connectors and remove the radio receiver assembly w/bracket.



9. REMOVE RADIO BRACKET NO.1

- (a) Remove the 4 screws and radio bracket No.1.



10. REMOVE RADIO BRACKET NO.2

- (a) Remove the 4 screws and radio bracket No.2.