

LUBRICATION

SERVICE DATA

0318B-01

Oil pressure at idle speed at 3,000 rpm	29 kPa (0.3 kgf/cm ² , 4.2 psi) or more 294 - 588 kPa (3.0 - 6.0 kgf/cm ² , 43 - 85 psi)												
Oil pump Tip clearance Side clearance Body clearance	<table border="0"> <tr> <td style="padding-right: 10px;">Standard</td> <td>0.06 - 0.16 mm (0.0024 - 0.0063 in.)</td> </tr> <tr> <td>Maximum</td> <td>0.16 mm (0.0063 in.)</td> </tr> <tr> <td style="padding-right: 10px;">Standard</td> <td>0.03 - 0.09 mm (0.0012 - 0.0035 in.)</td> </tr> <tr> <td>Maximum</td> <td>0.09 mm (0.0035 in.)</td> </tr> <tr> <td style="padding-right: 10px;">Standard</td> <td>0.250 - 0.325 mm (0.0098 - 0.0128 in.)</td> </tr> <tr> <td>Maximum</td> <td>0.325 mm (0.0128 in.)</td> </tr> </table>	Standard	0.06 - 0.16 mm (0.0024 - 0.0063 in.)	Maximum	0.16 mm (0.0063 in.)	Standard	0.03 - 0.09 mm (0.0012 - 0.0035 in.)	Maximum	0.09 mm (0.0035 in.)	Standard	0.250 - 0.325 mm (0.0098 - 0.0128 in.)	Maximum	0.325 mm (0.0128 in.)
Standard	0.06 - 0.16 mm (0.0024 - 0.0063 in.)												
Maximum	0.16 mm (0.0063 in.)												
Standard	0.03 - 0.09 mm (0.0012 - 0.0035 in.)												
Maximum	0.09 mm (0.0035 in.)												
Standard	0.250 - 0.325 mm (0.0098 - 0.0128 in.)												
Maximum	0.325 mm (0.0128 in.)												