

TORQUE SPECIFICATION

Part Tightened	N-m	kgf-cm	ft-lbf
Bleeder plug	11	112	8
Brake booster clevis lock nut	25.5	260	19
Brake pedal sub-assy x Brake pedal support sub-assy	34.3	350	25
Brake pedal support sub-assy x Body	14.2	145	10
Brake pedal support sub-assy x Brake pedal support reinforcement	34.3	350	25
Front disc brake cylinder x Steering knuckle	123	1,254	91
Flexible hose x Disc brake cylinder assy rear	31	316	23
Rear disc brake cylinder mounting x Axle hub	105	1,071	77
Rear disc brake cylinder mounting x Disc brake cylinder assy rear	88	897	65
Flexible hose x Disc brake cylinder assy rear	31	316	23
Brake booster pump x Brake booster accumulator	54	551	40
Brake master cylinder x Brake booster pump bracket No. 3	7.8	80	69 in. lbf
Brake master cylinder x Brake booster pump bracket No. 2	7.8	80	69 in. lbf
Brake booster pump x Brake booster pump bracket No. 1	7.8	80	69 in. lbf
Brake booster pump x Brake booster pump bracket No. 2	11.8	120	9
Brake booster pump x Brake booster pump bracket No. 3	11.8	120	9
Brake booster pump x Brake control wire	2.9	30	26 in. lbf
Brake master cylinder x Brake control wire	1.7	17	15 in. lbf
Brake master cylinder x Brake master cylinder union No. 1	32	326	23
Brake master cylinder x Brake master cylinder union No. 2	32	326	23
Brake union nut	15.2	155	11
Brake master cylinder x Brake actuator bracket No.4	7.8	80	69 in. lbf
Brake master cylinder x Brake actuator bracket No.1	7.8	80	69 in. lbf
Brake master cylinder x Master cylinder reservoir	1.7	17	15 in. lbf
Front speed sensor x Steering knuckle	8.3	85	73 in. lbf
Rear speed sensor x Axle hub	8.3	85	73 in. lbf
Yawrate sensor x Body	13	130	9
Skid control ECU assy set bolt	5.0	51	44 in. lbf
Junction block assy x Reinforcement	8.4	85	74 in. lbf