

TORQUE SPECIFICATION

Part Tightened	N-m	kgf-cm	ft-lbf
PROPELLER SHAFT ASSY FRONT			
Propeller shaft flange yoke x Companion flange	88	879	65
PROPELLER SHAFT ASSY			
Propeller shaft x Companion flange	88	897	65
FRONT AXLE HUB SUB-ASSY LH			
Front axle hub assy x Lock nut	235	2,396	173
Steering knuckle x Tie rod end	91	928	67
Steering knuckle x Stabilizer link	70	714	52
Disc brake caliper x Steering knuckle	123	1,254	91
Disc brake caliper x Brake tube	15	155	11
Front brake tube bracket set bolt	26	296	21
ABS speed sensor wire harness bracket set bolt	13	1,254	11
ABS speed sensor set bolt	8.3	85	73 in. lbf
Steering knuckle x Upper ball joint	110	1,122	81
Steering knuckle x Lower ball joint	225	2,294	166
Steering knuckle x Front axle w/ABS rotor bearing assy	80	816	59
Front wheel adjusting nut x Front axle w/ABS rotor bearing assy	275	2,804	203
Front wheel	112	1,142	83

SERVICE SPECIFICATIONS - DRIVE SHAFT, PROPELLER SHAFT, AXLE

Part Tightened	N·m	kgf·cm	ft·lbf
REAR AXLE SHAFT			
Axle housing x Rear axle shaft	123	1,254	91
Rear axle shaft w/backing plate x Disc brake caliper	47	480	35
ABS speed sensor set nut	8.3	85	73 in.·lbf
Rear brake tube x Master cylinder	15	155	11
Rear wheel	112	1,142	83