

TORQUE SPECIFICATION

| Part tightened | N·m | kgf·cm | ft·lbf |
|---|-------------------------------|--------|--------|
| Differential carrier assy front (1GR-FE (4WD)) | | | |
| Companion flange x Drive pinion | See page 29-3 | | |
| Propeller shaft x Companion flange | 88 | 897 | 65 |
| Differential front mounting support No. 1 x Frame | 137 | 1,400 | 101 |
| Differential front mounting support No. 2 x Frame | 137 | 1,400 | 101 |
| Differential front mounting support No. 2 x Front differential tube assy | 160 | 1,630 | 118 |
| Differential front mounting support No. 1 x Differential carrier assy front | 186 | 1,900 | 137 |
| Differential front mounting support No. 3 x Differential carrier assy front | 108 | 1,100 | 80 |
| Front differential mount nut No. 1 | 87 | 887 | 64 |
| Ring gear x Differential case | 97 | 985 | 71 |
| Differential carrier assy front x Breather tube | 13 | 133 | 10 |
| Differential carrier assy front x Side bearing retainer | 50 | 510 | 37 |
| Differential carrier assy front x Front differential tube assy | 110 | 1,120 | 81 |
| Differential vacuum actuator assy x Front differential tube assy | 21 | 210 | 15 |
| Drain plug | 65 | 660 | 48 |
| Filler plug | 39 | 400 | 29 |
| Front wheel | 112 | 1,142 | 83 |